



EU00060

## ENEOS Super Plus Diesel 20W50

### Motor Oil

ENEOS Super Diesel 20W50 is standard engine oil which ensures optimum lubrication for older passenger cars and light loaded commercial vehicles equipped with gasoline, LPG and diesel engines.. This Oil is suitable for use in engines with turbocharger, multi-valve technology and engine with a catalytic converter. In addition, this oil also contains special additives, which ensure that the oil does not thicken due to oxidation, even at high temperatures. Because of the stable Viscosity-Index improver, the viscosity will hardly decrease, as a result of which, this oil will also build strong film between moving parts.

#### ● SPECIAL FEATURES

##### 1. Excellent protection against wear, rust and corrosion

This Oil offers excellent protection against wear of all engine parts, which will also be protected against rust and corrosion. Special detergent/ dispersant properties keep ash and other dirt in suspension.

##### 2. Long Oil Drain Intervals

The formulation provides good lubrication film between the moving parts of the engine, resulting in long oil drain periods

#### ● PERFORMANCE LEVEL

API: CF-4/SG, CCMC G4/D4/PD-2  
VW 501/505, MB 228.1  
MIL-L-46152EC, MIL-L-2104D  
GM: 6085-M  
FORD: M2C-153C

#### ● APPLICATION

Motor oil for engines with turbocharger, multi-valve technology and engine with or without catalytic converter.

#### ● CONTAINERS

1L, 4L, 18L Tin or 20L Pail, 200L, 1000L IBC

#### ● TYPICAL PROPERTIES

|  |        |
|--|--------|
| SAE viscosity grade                            | 20W-50 |
| Density (20°C), g/cm <sup>3</sup>              | 0.886  |
| Flash point (COC), °C                          | 232    |
| Kinematic viscosity (40°C), mm <sup>2</sup> /s | 147    |
| (100°C), mm <sup>2</sup> /s                    | 17.1   |
| Viscosity index                                | 129    |
| Pour point, °C                                 | -24.0  |

Note: The typical properties may be changed without notice.  
(February 2006)

THE RECOMMENDATIONS OR SUGGESTIONS MADE IN THIS SHEET ARE MADE WITHOUT GUARANTEE OR REPRESENTATION AS TO RESULTS. THE CONTENT OF THIS SHEET IS CORRECT TO THE BEST OF OUR KNOWLEDGE. WE ADVISE THE READER TO CAREFULLY EVALUATE THE PRODUCT CHOICE FOR CRITICAL APPLICATIONS TOGETHER WITH THE SUPPLIER. WE DO NOT ACCEPT RESPONSIBILITY FOR DAMAGE AS A CONSEQUENCE OF INCOMPLETENESS OR NEGLIGENCE AND INACCURACIES IN THIS INFORMATION SHEET. ALL TERMS OF SALE OF THE SUPPLIER CAN BE APPLIED HERE.