



EU00061

ENEOS Premium 20W50

Synthetic Motor Oil for Mixed Fleets

ENEOS Premium 20W50 is a robust synthetic engine oil, developed according to the latest oil-consumption- and exhaust emission norms. It is especially suitable for mixed fleet applications, like gasoline, LPG and light diesel engines, with or without turbo and/or catalytic converter. Because of this broad applicability the oil stock of different qualities can be reduced considerably at the wholesaler or fleet-owner.

● SPECIAL FEATURES

1. Special Deposit Control Formulation

This Oil fulfils the latest strict norms concerning deposits on the piston crown, the upper piston-ring groove and the rest of the pistons.

2. Keep engine and oils in perfect condition

Because of its stability against high temperatures and ageing as well as due to the strongly cleaning additives ENEOS Premium 20W50 makes sure that the engine and its oil stay in perfect condition.

● PERFORMANCE LEVEL

API: CG-4/SJ

ACEA: A2/B3/E2

Volkswagen 501.01/505.00

MB: 228.1 229.1

Volvo: VDS,

MAN: 271,

Mack: EO/L

● APPLICATION

Mixed fleet applications, like gasoline, LPG and light diesel engines, with or without turbo and/or catalytic converter

● CONTAINERS

1L, 4L, 18L Tin / 20L Pail, 200L, 1000L IBC

● TYPICAL PROPERTIES

| SAE viscosity grade | 20W-50 |
|--|--------|
| Density (20°C), g/cm ³ | 0.883 |
| Kinematic viscosity (40°C), mm ² /s | 162.1 |
| (100°C), mm ² /s | 18.1 |
| Viscosity index | 124 |
| Pour point, °C | -25 |
| Viscosity(-20°C), mPa.s | <9,500 |

Note: The typical properties may be changed without notice. (November 2006)